



- Features:**
- Securable side panels (from inside). Easy to lift and remove.
 - 3-point, keyed locks on front and rear doors. Available in multiple key-codes.
 - Set of four (4) mounting uprights interchangeable to either 19" or 23" rack-mount orientation with cable management slots for cable ties.
 - Quick-release, spring-hinged doors for easy access for setup and maintenance.
 - ¼"-20 grounding points located throughout enclosure.
 - No side cross-bracing for quick and easy side access.
 - Open base design for under-floor cable routing.

- Materials:**
- Frame : 11 gauge steel fully welded chassis
 - Doors : 13 gauge steel Side
 - Panels : 16 gauge steel
 - Mounting Uprights : Zinc-plated 11 gauge steel

S84	30	48	D	E	F	XX
s84: 84" high seismic cabinet					F: MOUNTING HOLE PATTERN 0 = 1" hole spacing 1 = 1 ¼" - ½" EIA wide spacing 2 = EIA Universal	64 = Blue Wrinkle 45 = Black Wrinkle 44 = Gray
30" width						
48" deep						
D : FAN OPTION 0 = No fan / louvered top panel 1 = Four (4) AC fans @ 408 CFM				E : DOOR CONFIGURATION 0 = Solid front & rear doors with louvers and solid sides 1 = Perforated front & rear doors and solid sides 9 = No Doors (front / back) or sides/top panels. *** note: side panels can be ordered separately with part number xxxxxxxxxx. Doors can only be ordered at original time of purchase and can not be added at a later time.		